



Toilet close-coupled	Dimension	Weight	Order number
(without cistern), washdown model, Outlet for Vario connector set, for horizontal and vertical outlet, length adjustable from 7 - 170 mm, and vario connecting bend, vertical outlet from 160 220 mm, fixings included, UWL class 1			
Colors			
00 White Alpin 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)	9		
Variant			
<b>♦</b> 4,5 l	370 x 630 mm	30.500 kilogram	21550900
Sanitary ceramics with the special WonderGliss surface finish witime to come.  When ordering WonderGliss please add a "1" as eleventh digit.		ittractive-looking for a lon	9
		ttractive-looking for a lon	9
time to come. When ordering WonderGliss please add a "1" as eleventh digit		ittractive-looking for a long	899025
time to come. When ordering WonderGliss please add a "1" as eleventh digit  Accessory	to the model number.		
time to come. When ordering WonderGliss please add a "1" as eleventh digit  Accessory  Vario connecting bend for vertical outlet	to the model number. Ø 100 mm	0.700 kilogram	899025
time to come. When ordering WonderGliss please add a "1" as eleventh digit  Accessory  Vario connecting bend for vertical outlet  Vario connector set incl. excenter	to the model number. Ø 100 mm	0.700 kilogram	899025
time to come. When ordering WonderGliss please add a "1" as eleventh digit  Accessory  Vario connecting bend for vertical outlet  Vario connector set incl. excenter  Suitable products  Toilet seat and cover hinges stainless steel, without soft	to the model number. Ø 100 mm	0.700 kilogram	899025 001422



## DuraStyle Toilet close-coupled # 215509..00

|< 370 mm >|

Cistern with Dual Flush mechanism, chrome, for bottom left supply, 390 x 170 mm	390 x 170 mm	093510
Toilet seat and cover with lateral reinforcement and extended hinge shaft, hinges stainless steel, without soft closure,		002061

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished ceramic piece.