

INSTALLATION SYSTEMS, WC-SYSTEM FOR DRY-WALL CONSTRUCTION, ACCESSORIES VICONNECT

PRODUCT INFORMATION

1 . POSITION



Model	922461
Width	525 mm
Height	1 120 mm
Depth	135 mm
Weight	12 kg
Description	<p>for dry-wall construction, standard height for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, adjustment range front to wall: 135-205mm (when mounted on wall brackets) 4-point fastening with wall brackets, includes support feet and fastening materials, with protection cap for the flushing pipe, 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts, installation instructions, without flush plate Individual packaging materials For combination with: for wall-mounted WC self-supporting powder-coated steel frame, fully pre-assembled front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint, with protection cap for the flushing pipe concealed cistern with insulation against condensation with dual flush 3/6l, adjustable to 3/4,5l, maximal flush quantity 7,5l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, 2-part angle valve connection set R1/2, mounting clip for drain bend, 4 adjustment settings, protection box for access opening can be cut to size, with depth-adjustable WC connecting bend 90° DN 90 (Ø90) / with reducing sleeve DN 90 (Ø90)/DN 100 (Ø110) with protection cap, complete WC connection set DN 90 (Ø90)/ 180mm, certification marks for concealed cistern: Noise Class I,</p>

Specification texts

ViConnect; WC element; Size: 525 x 1120 x 135 mm; for dry-wall construction, standard height; for covering with plasterboard, installation onto a solid brick wall, in dry-wall constructions etc., adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200mm, adjustment range front to wall: 135-205mm (when mounted on wall brackets); 4-point fastening; with wall brackets, includes support feet and fastening materials, with protection cap for the flushing pipe, 2 times M12 WC retaining bolts adjustable to 180mm with protection plugs and nuts, installation instructions, without flush plate; Individual packaging materials; For combination with: for wall-mounted WC; self-supporting powder-coated steel frame, fully pre-assembled; front operated, button function transmitted to drain fitting via flexible cables, connection to flush plate via bayonet joint, with protection cap for the flushing pipe; concealed cistern with insulation against condensation with dual flush 3/6l, adjustable to 3/4, 5l, maximal flush quantity 7,5l, filling valve Noise Class I, flexible hose for filling valve, can be tightened by hand, 2-part angle valve connection set R1/2, mounting clip for drain bend, 4 adjustment settings, protection box for access opening can be cut to size, with depth-adjustable WC connecting bend 90° DN 90 (Ø90) / with reducing sleeve DN 90 (Ø90)/DN 100 (Ø110) with protection cap, complete WC connection set DN 90 (Ø90)/180mm, certification marks for concealed cistern: Noise Class I,

COLOURS

92246100 4051202339630

TECHNICAL DRAWINGS

922461

